MEMBRANE SENSOR MTP-L

This low-wear membrane sensor designed for analog and absolute measurements is characterised by a good resolution and is hermetically sealed.
Contact is achieved via a spring loaded pin.

This product offers a high degree of customization.

Advantages
– Adjustable measuring range: 30–500 mm
– Simple assembly, self-adhesive
– Particularly flat design, less than 1 mm thick
– Good resolution, precision and measurement accuracy

Application examples
– Medication pumps
– Alignment of antennas
– Cylinder stroke measurement
– Valve adjustment



General data	
Sensor technology	Potentiometric
Type of contact	Spring loaded pin
Sensor type	Absolute measuring
Curcuit	As voltage divider

Electrical data	
Measuring range	30 to 500 mm, adjustable
Independent linearity	± 2 %
Resolution	0.05 mm achievable
Resistance range	2.5 kΩ per 100 mm travel
Resistance tolerance	± 30 %
Max. wiper current	5 mA in case of malfunction
Supply voltage	5 VDC typ., 3 to 30 VDC possible
Output signal	Analog 0 to 100 % of supply voltage

Mechanical data	
Dimensions	See drawings
Sensor thickness	0.8 mm
Travel speed	1 m/sec
Actuation force	1 to 3 N
Spring loaded pin	With spring-loaded POM ball, external thread M6
Mounting	Self-adhesive
Lifetime	> 5 million cycles


Environmental data	
Operating temperature	-25 °C to +85 °C
Protection class acc. to IEC 60529	IP 65*
EMC	Uncritical
ESD	Uncritical

Material	
Basic material	Polyester Other materials on request
Spring loaded pin	Stainless steel and POM ball

Electrical connection	
	Crimp contact Solder pad Connector Pitch 2.54 mm

* except for electrical connection and connector

MEMBRANE SENSOR MTP-L



All dimensions in mm

Installation instructions


To install the sensor, remove the protective film on the rear side.
To ensure proper installation and function, the surface to which the sensor is to be applied must meet the following properties:
– be flat and smooth
– be free of moisture, oil, grease, and dust

Please use a suitable cleaning agent, for example, isopropanol or MEK, to clean the carrier material. Avoid temperature differences between the sensor and the carrier material.


Adhesive tape: The recommended processing temperature is 18°C to 35°C.

Storability is 2 years at room temperature and a humidity of 50 to 70%.


Electrical connection



Connector




Solder pad / Crimp contact



Spring loaded pin

Metallux spring loaded pin with POM ball
Article No. H959000000

Requirements for the spring loaded pin:
– The contact surface of the ball should preferably be made of POM to achieve low friction coefficients
– Recommended ball diameter: 3 to 10 mm
– Recommended actuation force: approx. 1 to 3 N



When selecting the spring loaded pin, consider the sensor width, foil material, and travel speed.

Sample order

Article No.	Product name	Measuring range	Electrical connection
E080200100	MTP-L	100 mm	Crimp contact
H959000000	Spring loaded pin		

Metallux cannot picture the customer's operating and application conditions and the customer's existing environmental influences.
We therefore recommend that you carry out your own investigations into the planned use of the products under the actual operating conditions.

We continuously improve our products and also update our data sheets regularly. In this respect, there may be changes in the specification.
These changes will apply to orders received by us from the time of the update, unless otherwise agreed.

Our products comply with Directive 2011/65/EU (RoHS) including Directive 2015/863/EU and Regulation (EC) No. 1907/2006 (REACH).